

CRX-10iA/L




Max. load capacity
at wrist: **10 kg**



Max. reach:
1418 mm

Controlled axes	Repeatability (mm)	Mechanical weight (kg)	Motion range [°]						Maximum speed [°/s] *2						J4 Moment/Inertia (Nm/kgm ²)	J5 Moment/Inertia (Nm/kgm ²)	J6 Moment/Inertia (Nm/kgm ²)
			J1	J2	J3	J4	J5	J6	J1	J2	J3	J4	J5	J6			
6	± 0.05	≤ 39*1	360	360	540	380	360	380	120	120	180	180	180	180	34.8/1.28	26.0/0.90	11.0/0.30

Working range



Robot

CRX-10iA/L

190

Robot footprint [mm]

●

Mounting position Floor

●

Mounting position Upside down

●

Mounting position Angle *3

●



Controller

R-30iB Plus

●

Mini Plus

420 x 290 x 370

Dimentions [mm]

●

Tablet TP

Electrical connections

Voltage 50/60Hz 3phase [V]

-

Voltage 50/60Hz 1phase [V]

200-230

Average power consumption [kW]

0.5

Environment

Ambient temperature [° C]

0-45

Ambient humidity [%]

≤ 75 *4

Ambient humidity - Short term [%RH]

≤ 95 *5

Vibration acceleration [m/s²]

≤ 4.9 (0.5G)

Protection

IP54

*1) Without controller. Weight of controller ≤ 19 kg.

*2) During short distance motions, the speed may not reach the maximum value stated.

*3) In case of angle mount, motion range needs to be restricted according to the payload.

*4) No dew nor frost allowed.

*5) Within one month.

● standard ○ on request - not available () with hardware and/or software option